


## Features

1. Monolithic inorganic material construction.
2. Closed magnetic circuit avoids crosstalk.
3. S.M.T. type.
4. Suitable for reflow soldering.
5. Shapes and dimensions follow E.I.A. spec.
6. Available in various sizes.
7. Excellent solder ability and heat resistance.
8. High reliability. Reliability test meet AEC-Q200.
9. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
10. Operating Temperature: -55~+125°C (Including self-temperature rise)



Certificate  
of  
Green Partner


## Dimensions



Chip Size	
A	1.00±0.10
B	0.50±0.10
C	0.50±0.10
D	0.25±0.10

Units: mm

## Part Numbering



- A: Series  
 B: Dimension L x W  
 C: Category Code V=Vehicle  
 D: Inductance 1R0=1.0uH  
 E: Inductance Tolerance K=±10%, L=±15%, M=±20%

## Specification

Tai-Tech Part Number	Inductance		Q		Rated Current (mA) max.	DCR (Ω) max.	SRF (MHz) min.
	uH	Test Frequency (Hz)	min.	Test Frequency (MHz)			
FCI1005V-1R0□	1.0	60mV / 10M	20	10	15	0.90	40
FCI1005V-1R8□	1.8	60mV / 10M	20	10	15	1.45	30
FCI1005V-2R2□	2.2	60mV / 10M	20	10	10	1.70	28

NOTE: □: TOLERANCE K=±10%, L=±15%, M=±20%

**Q vs Frequency,DC Bias Characteristics(Typical)**

