

SMD Power Inductor


HPC6020NF-SERIES

1. Features

1. This specification applies Low Profile Power Inductors.
2. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
3. Operating temperature :-40~+125°C (Including self - temperature rise).




2. Dimension



Series	*A(mm)	*B(mm)	*C(mm)	D(mm)	E(mm)	F(mm)
HPC6020NF	6.0±0.2	6.0±0.2	1.8±0.2	1.6±0.3	5.8±0.3	4.3ref

*Dimensions are not including the termination. For maximum overall dimensions with termination, add 0.1mm.

Recommend Land pattern



G(mm)	H(mm)	I(mm)
2.5	5.8	1.8

Note: 1. The above PCB layout reference only.
2. Recommend solder paste thickness at 0.15mm and above.

3. Part Numbering



- A: Series
- B: Dimension
- C: Type
- D: Inductance
- E: Inductance Tolerance

A/B*C

1R0=1.00uH, 100=10uH, 101=100uH, 102=1000uH
K=±10%, L=±15%, M=±20%, Y=±30%.

marking direction cannot decide polarity. Color: Black, unidirectional.
magnetic shielding

4. Specification

Part Number	Inductance L0 (uH) @ 0 A	Tolerance				Rated current		DCR (mΩ) @25°C ±20%.
						Temperature current I rms (A)	Saturation current I sat (A)	
		K	L	M	Y			
HPC6020NF-R80	0.80	/	/	±20%	±30%	5.5	7.5	16
HPC6020NF-1R0	1.00	/	/	±20%	±30%	4.5	6.2	19
HPC6020NF-1R5	1.50	/	/	±20%	±30%	3.8	5.5	22.5
HPC6020NF-2R0	2.00	/	/	±20%	±30%	3.65	5.3	25
HPC6020NF-2R2	2.20	/	/	±20%	±30%	3.5	5.0	29
HPC6020NF-3R3	3.30	/	/	±20%	±30%	3.3	4.0	35
HPC6020NF-4R7	4.70	/	±15%	±20%	±30%	2.8	3.0	54
HPC6020NF-5R6	5.60	/	±15%	±20%	±30%	2.6	2.7	59
HPC6020NF-6R8	6.80	/	±15%	±20%	±30%	2.5	2.6	78
HPC6020NF-8R2	8.20	/	±15%	±20%	±30%	2.3	2.4	103
HPC6020NF-100	10.0	±10%	±15%	±20%	±30%	2.1	2.1	106
HPC6020NF-150	15.0	±10%	±15%	±20%	±30%	1.6	1.5	138
HPC6020NF-220	22.0	±10%	±15%	±20%	±30%	1.4	1.3	204
HPC6020NF-330	33.0	±10%	±15%	±20%	±30%	1.3	1.2	340

Note:

- All test data referenced to 25°C ambient , Ls:100KHz/1V.
- Testing Instrument : HP4284A,CH11025,CH3302,CH1320 ,CH1320S LCR METER / Rdc:CH502BC MICRO OHMMETER.
- Heat Rated Current (Irms) will cause the coil temperature rise approximately Δt of 40°C.
- Saturation Current (Isat) will cause L0 to drop approximately 30%.
- Rated DC Current : The less value which is I rms or Isat.
- The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions.Circuit design,component,PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
- Special inquiries besides the above common used types can be met on your requirement.

5. Typical Performance Curves

