


1. Features

- 1.Low DC resistance structure of electrode to prevent wasteful electric power consumption.
- 2.Suitable for reflow soldering.
- 3.Excellent solder ability and heat resistance.
- 4.100% Lead(Pb) & Halogen-Free and RoHS compliant.
- 5.Operating Temperature:-55~+105°C (Including self-temperature rise)



Certificate
of
Green Partner

2. Dimensions



Chip Size				
Series	A(mm)	B(mm)	C(mm)	D(mm)
201610	2.00±0.20	1.60±0.20	1.00 max.	0.50±0.30

3. Part Numbering

MPI
201610
M
F
 -
 2R2
M
 -
 1A2

A B C D E F G

A: Series
 B: Dimension
 C: Category Code
 D: Material
 E: Inductance
 F: Inductance Tolerance
 G: Rated Current

Lead Free Material
 2R2=2.20uH
 M=±20%

4. Specification

Tai-Tech Part Number	Inductance(uH)	Test Frequency (Hz)	Rated Current (mA) max.	DCR(Ω)	
				max.	typ.
MPI201610MF-1R0M-1A4	1.00±20%	1M / 60mV	1400	0.14	0.11
MPI201610MF-1R5M-1A2	1.50±20%	1M / 60mV	1200	0.19	0.15
MPI201610MF-2R2M-1A2	2.20±20%	1M / 60mV	1200	0.26	0.20
MPI201610MF-4R7M-1A1	4.70±20%	1M / 60mV	1100	0.45	0.35

- Irms:DC current that causes temperature rise(ΔT 40°C) from 25°C ambient.