

SMD Power Inductor

TMPF0402A-Series(N)-D

1. Features


1. Soft saturation.
2. High current , low DCR , high efficiency.
3. Very low acoustic noise and very low leakage flux noise.
4. High reliability.
5. 100% Lead(Pb)-Free and RoHS compliant.
6. Operating temperature -40~+125°C(Including self - temperature rise)



2. Applications

Note PC power system , incl. IMVP-6
DC/DC converter .


Recommend PC Board Pattern



L(mm)	G(mm)	H(mm)
3.6 ref	1.4 ref	3.8 ref


Note: 1、 The above PCB layout reference only.
2、 Recommend solder paste thickness at 0.12mm and above.

3. Dimensions




Series	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)
TMPF0402A	4.1±0.2	4.1±0.2	1.9±0.2	3.4±0.3	0.88±0.2	1.6±0.25

4. Part Numbering



A: Series
B: Dimension
C: Type
D: Inductance
E: Inductance Tolerance
F: Code

BxC
Material.
1R0=1.00uH
M=±20%
Marking: Black.1R0 and 2019(20 YY, 19 WW, follow production date).



DCR Test

5. Specification

Part Number	Inductance (uH) $\pm 20\%$ @ 0 A	I rms (A)		I sat (A)	DCR(m Ω) Typ.	DCR(m Ω) Max.
		20 $^{\circ}$ C rise	40 $^{\circ}$ C rise			
TMPF0402A-R10MN-D	0.10	13.5	18.0	38.0	2.2	2.42
TMPF0402A-R22MN-D	0.22	13.0	16.8	19.5	4.1	4.6
TMPF0402A-R33MN-D	0.33	12.0	15.5	18.0	5.0	5.5
TMPF0402A-R36MN-D	0.36	11.0	14.5	17.0	5.6	6.3
TMPF0402A-R40MN-D	0.40	10.0	14.0	15.5	6.9	7.73
TMPF0402A-R56MN-D	0.56	8.5	12.0	14.0	8.4	9.30
TMPF0402A-R60MN-D	0.60	8.0	11.7	13.7	8.6	9.52
TMPF0402A-R72MN-D	0.72	7.6	10.5	12.0	10.4	11.6
TMPF0402A-1R0MN-D	1.00	6.8	9.6	9.6	13.3	14.6
TMPF0402A-1R2MN-D	1.20	6.6	9.0	9.0	16.2	17.9
TMPF0402A-1R5MN-D	1.50	5.8	7.6	8.0	21.0	23.5

Note:

1. Test frequency : L : 100KHz /0.1V.
2. All test data referenced to 25 $^{\circ}$ C ambient.
3. Testing Instrument : L: HP4284A,HP4395A,CH11025,CH3302,CH1320 ,CH1320S LCR METER / Rdc:CH16502,Agilent33420A MICRO OHMMETER,or EQU.
4. Current that causes the specified temperature rise from 25C ambient.
5. Saturation Current (Isat) will cause L0 to drop approximately 30%.
6. The part temperature (ambient + temp rise) should not exceed 125 $^{\circ}$ C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
7. Special inquiries besides the above common used types can be met on your requirement.
8. Rated operating voltage(across inductor) 15V ref (1.5uH and above) .
Rated operating voltage(across inductor) 40V ref (1.2uH and below).

6. Typical Performance Curves

